



**MINOR 2003**



▪ Robust, versatile and easy to install. The perfect solution for construction hoisting needs.

▪ Robuste, polyvalent et facile à installer, la solution parfaite aux besoins de levage dans la construction.



Security hook  
Crochet de sécurité



Top limit switch  
Fin de course supérieure

**SPECIFICATIONS**

**CARACTÉRISTIQUES**

**MINOR 2003**

Lifting capacity  
Lifting speed  
Cable length  
Cable diameter  
Cable rupture load  
Motor power rating  
Single-phase motor voltage  
Handling voltage  
Rotation radius  
Rotation angle  
Weight  
Width  
Length  
Height  
Volume

*Puissance de levage*  
*Vitesse de levage*  
*Longueur de câble*  
*Diamètre du câble*  
*Charge de rupture du câble*  
*Puissance moteur*  
*Tension moteur monophasé*  
*Tension manoeuvre*  
*Rayon de rotation*  
*Angle de rotation*  
*Poids*  
*Largueur*  
*Longueur*  
*Hauteur*  
*Volume*

300 Kg  
24 m/min  
30/40 m  
5 mm  
1980 Kg  
1,5 HP/CV  
220 V  
220 V  
1.160 mm  
200 °  
60 Kg  
390 mm  
1210 mm  
620 mm  
0,27 m³

